

1-15369

IN THE CLAIMS

1.-33. (Cancelled).

34. (Currently amended) An apparatus for treating gas with at least one agent, and ~~then heating the gas to a predetermined temperature if desired~~, the gas being received into the apparatus from a gas source, the apparatus comprising:

- a) a housing having an inlet and an outlet;
- b) a single chamber within said housing having an entry port and an exit port, the entry port for connection to a gas source to receive therefrom a gas stream; and the exit port for exit removal of the gas stream from the single chamber ~~carrying an admixed agent from the housing~~; and
- c) a first quantity of a pharmacologic agent contained within the chamber and positioned such that a portion of the pharmacologic agent may be ~~to be~~ admixed with and carried by the gas stream through the exit port.

35. (Currently Amended) The apparatus defined in Claim 34, and further comprising a container containing a second quantity of the pharmacologic an agent, the container in fluid communication with the chamber.

36. (Withdrawn) The apparatus defined in Claim 35, wherein the container comprises an opening that releases the agent into the chamber.

37. (Withdrawn) The apparatus defined in Claim 35, wherein the container is pre-filled with a quantity of an agent.

38. (Previously Presented) The apparatus defined in Claim 35, wherein the container comprises a port to receive a quantity of an agent.

1-15369

39. (Currently Amended) The apparatus defined in Claim 34, and further comprising at least one layer of an absorbent material positioned inside the chamber to absorb ~~retain~~ a quantity of an the pharmacologic agent.

40. (Withdrawn) The apparatus defined in Claim 35, wherein the container further comprises a bag member suitable for containing a quantity of an agent and having an opening that is sized so as to permit release of a quantity of agent from the bag member into the chamber for treating the gas with the agent.

41. (Withdrawn) The apparatus defined in Claim 40, wherein the container comprises a bag member positioned inside the chamber suitable for containing a quantity of an agent, the bag member being formed of a semi-permeable material so that the gas stream flowing through the chamber is treated with the agent contained within the bag.

42. (Withdrawn) The apparatus defined in Claim 34, and further comprising:

- a) at least one bag member in the single chamber having an opening that is sized so as to permit release of a quantity of agent therefrom;
- b) at least one layer of absorbent material in the single chamber; and
- c) a tube member having first and second ends, the first end being coupled to the opening of the bag member and the second end being positioned proximate to the at least one layer so as to deliver the agent onto the layer.

43. (Withdrawn) The apparatus defined in Claim 40, wherein the bag member is disposed inside the chamber or outside the chamber.

44. (Withdrawn) The apparatus defined in Claim 35, wherein the container comprises an elongated tube member extending inside the chamber and having a proximal and a distal end,

1-15369

a restrictive opening being provided in the elongated tube member to release one or more agents into the chamber when the elongated tube member is filled with a quantity of an agent.

45. (Withdrawn) The apparatus defined in Claim 35, and further comprising a pressurizer for pressurizing the agent inside the container, wherein the container comprises a valve for releasing the quantity of agent into the chamber in response to pressure inside the container.

46. (Withdrawn) The apparatus defined in Claim 45, wherein the container is positioned inside or outside the chamber.

47. (Withdrawn) The apparatus defined in Claim 35, wherein the container comprises an inkjet print head having at least one nozzle coupled to an opening on the housing for releasing vapor bubbles of at least one agent into the chamber through the opening when energized by control signals.

48. (Withdrawn) The apparatus defined in Claim 47, and further comprising:

- a) at least one reservoir associated with the inkjet print head for containing a volume of one or more agents; and
- b) a controller coupled to the inkjet print head and supplying control signals to the inkjet print head to control the release of one or more agents from the inkjet print head into the chamber.

49. (Currently Amended) The apparatus defined in Claim 34, and further comprising:

- a) a back-up or reserve supply container; and

1-15369

b) an access tubing connecting said back up or reserve container to a charging port in fluid communication with the single chamber ~~that is attached to a lateral extension of said housing.~~

50. (Previously Presented) The apparatus defined in Claim 49, wherein the backup or reserve supply container hangs free of the apparatus.

51. (Previously Presented) The apparatus defined in Claim 49, wherein the backup or reserve supply container is attached to a portion of the apparatus.

52. (Currently Amended) The apparatus defined in Claim 34, and further comprising ~~humidity sensing means~~ a humidity sensor positioned in the single chamber in the flow path of the gas stream.

53. (Currently Amended) The apparatus defined in Claim ~~34~~ 52, and further comprising a heating element ~~heating means~~ disposed within the chamber ~~for heating the gas.~~

54. (Currently Amended) The apparatus defined in Claim 53, and further comprising:

- a) a temperature sensor ~~temperature sensing means~~ disposed within the chamber. ~~for sensing the temperature of the gas in the chamber; and~~
- b) ~~control means connected to the temperature sensing means and to the heating means and responsive to the temperature sensing means to control electrical power to the heating means so as to regulate the amount of heat applied by the heating means to the gas within the chamber.~~

55. (Currently Amended) An apparatus for treating gas with a humidifying solution and at least one pharmacologic agent, ~~and then heating the gas to a predetermined temperature if desired,~~ the gas being received into the apparatus from a gas source, the apparatus comprising:

1-15369

- a) a housing having an inlet and an outlet;
- b) a single chamber within said housing having an entry port communicating with the inlet of the housing and an exit port communicating with the outlet of the housing, the entry port for connection to a gas source to receive therefrom a gas stream;
- c) a first quantity of the humidifying solution contained within the single chamber and positioned such that a portion of the humidifying solution may be admixed with and carried by the gas stream through the exit port; ~~a quantity of the humidifying solution admixed with and carried by the gas stream in said single chamber;~~
- d) a first quantity of a pharmacologic agent contained within the single chamber and positioned such that a portion of the pharmacologic agent may be admixed with and carried by the gas stream through the exit port ~~a quantity of the at least one agent to be admixed with and carried by the gas stream in said single chamber;~~ and
- e) a backup or reserve supply container for the at least liquid agent and/or humidifying solution in fluid communication with said chamber.

56. (Currently Amended) The apparatus defined in Claim 55, and further comprising at least one container for containing a quantity of the ~~a~~ humidifying solution and a quantity of the ~~pharmacologic an~~ agent, the at least one container in fluid communication with the single chamber.

1-15369

57. (Withdrawn) The apparatus defined in Claim 56, wherein the at least one container comprises an opening that releases the humidifying solution and/or the agent into the chamber.

58. (Withdrawn) The apparatus defined in Claim 56, wherein the at least one container is pre-filled with a quantity of a humidifying solution and/or an agent.

59. (Currently Amended) The apparatus defined in Claim 56, wherein the at least one container comprises a port to receive a at least some of either or both of the quantity of a humidifying solution or an the pharmacologic agent.

60. (Currently amended) The apparatus defined in Claim 55, and further comprising at least one layer of an absorbent material positioned inside the single chamber to absorb retain a at least a portion of the first quantity of the pharmacologic an agent.

61. (Withdrawn) The apparatus defined in Claim 56, wherein the at least one container comprises separate bag members, one suitable for containing a quantity of humidifying solution, and at least one suitable for containing a quantity of an agent, each having an opening that is sized so as to permit release of a quantity of humidifying solution or agent from the bag member into the chamber for treating the gas.

62. (Withdrawn) The apparatus defined in Claim 56, wherein a bag member is positioned inside the chamber and is formed of a semi-permeable material so that the gas stream flowing through the chamber is treated with the humidifying solution or agent contained within the bag.

63. (Withdrawn) The apparatus defined in Claim 61, wherein the separate bag members are positioned outside of the chamber.

1-15369

64. (Withdrawn) The apparatus defined in Claim 63, and further comprising at least one tube member having first and second ends, the first end being coupled to the opening of one of the bag members and the second end being coupled to an opening on the housing that releases the contents of the bag member into one of the plurality of separate chambers inside the housing.

65. (Withdrawn) The apparatus defined in Claim 56, wherein the at least one container comprises separate elongated tube members extending inside the chamber and having a proximal and a distal end, a restrictive opening being provided in each elongated tube member to release humidifying solution or agent into the chamber, one elongated tube member being filled with a quantity of humidifying solution and at least one additional elongated tube member being filled with an agent.

66. (Withdrawn) The apparatus defined in Claim 56, and further comprising a pressurizer for pressurizing the agent inside the container, wherein the at least one container comprises a valve for releasing a quantity of humidifying solution and at least one agent into the chamber in response to pressure inside the container.

67. (Withdrawn) The apparatus defined in Claim 66, wherein the elongated tube member is positioned outside the chamber.

68. (Withdrawn) The apparatus defined in Claim 56, wherein the at least one container comprises an inkjet print head having at least one nozzle positioned proximate to at least one opening of the housing for releasing vapor bubbles of humidifying solution and at least one agent into the chamber through the opening when energized by control signals.

1-15369

69. (Withdrawn) The apparatus defined in Claim 68, and further comprising:

- a) at least one reservoir associated with the inkjet print head for containing a volume of humidifying solution or one or more agents; and
- b) a controller coupled to the inkjet print head and supplying control signals to the inkjet print head to control the release of humidifying solution and one or more agents from the inkjet print head into the chamber.

70. (Currently Amended) The apparatus defined in Claim 55, and further comprising an access tubing connecting the backup or reserve supply container to a charging port in fluid communication with the single chamber ~~that is attached to a lateral extension of said housing.~~

71. (Previously Presented) The apparatus defined in Claim 55, wherein the backup or reserve supply container hangs free of the apparatus.

72. (Previously presented) The apparatus defined in Claim 55, wherein the backup or reserve supply container is attached to a portion of the apparatus.

73. (Currently Amended) The apparatus defined in Claim ~~55~~ 72, and further comprising a humidity sensor ~~humidity sensing means~~ positioned in the single chamber in the flow path of the gas stream.

74. (Currently Amended) The apparatus defined in Claim ~~55~~ 73, and further comprising a heating element ~~heating means~~ disposed within the single chamber ~~for heating the gas.~~

75. (Currently Amended) The apparatus defined in Claim 74, and further comprising:

- a) a temperature sensor ~~sensing means~~ disposed within the single chamber.
~~for sensing the temperature of the gas in the chamber; and~~

1-15369

~~b) control means connected to the temperature sensing means and to the heating means and responsive to the temperature sensing means to control electrical power to the heating means so as to regulate the amount of heat applied by the heating means to the gas within the chamber.~~

76. (Withdrawn) An apparatus for treating gas with a humidifying solution and at least one agent, and then heating the gas to a predetermined temperature if desired, the gas being received into the apparatus from a gas source, the apparatus comprising:

- a) a housing having an inlet and an outlet; and
- b) a plurality of separate chambers within said housing, each separate chamber having an entry and exit port through which the gas stream flows, and a separate port to receive a quantity of an agent to be admixed with the gas stream, the entry port of at least one of the separate chambers connected to a gas source to receive therefrom a gas stream and the exit port of another separate chamber for removal of the gas stream carrying one or more admixed agents from the housing.

77. (Withdrawn) The apparatus defined in Claim 76, and further comprising at least one container for containing a quantity of an agent, the at least one container in fluid communication with at least one of the plurality of separate chambers within the housing.

78. (Withdrawn) The apparatus defined in Claim 77, wherein the at least one container comprises an opening in each of the separate chambers that releases an agent into each chamber.

79. (Withdrawn) The apparatus defined in Claim 77, wherein the at least one container is pre-filled with a quantity of an agent.

1-15369

80. (Withdrawn) The apparatus defined in Claim 77, wherein the at least one container comprises a port associated with each of the separate chambers to receive a quantity of an agent.

81. (Withdrawn) The apparatus defined in Claim 76, and further comprising at least one layer of an absorbent material positioned inside each separate chamber to retain a quantity of an agent.

82. (Withdrawn) The apparatus defined in Claim 77, wherein the container comprises a bag member suitable for containing a quantity of an agent and having an opening that is sized so as to permit release of a quantity of agent from the bag member into each of the separate chambers for treating the gas with the agent.

83. (Withdrawn) The apparatus defined in Claim 82, wherein a bag member is positioned inside each of the separate chambers and is formed of a semi-permeable material so that the gas stream flowing through each chamber is treated with the agent contained within the bag.

84. (Withdrawn) The apparatus defined in Claim 82, wherein at least one bag member is positioned outside the plurality of chambers.

85. (Withdrawn) The apparatus defined in Claim 83, and further comprising at least one tube member having first and second ends, the first end being coupled to the opening of one of the bag members and the second end being coupled to an opening on the housing that releases the agent into one of the separate chambers.

86. (Withdrawn) The apparatus defined in Claim 77, wherein the at least one container comprises an elongated tube member extending inside each chamber and having a

1-15369

proximal and a distal end, a restrictive opening being provided in each elongated tube member to release one or more agents into each chamber when the elongated tube member is filled with a quantity of an agent.

87. (Withdrawn) The apparatus defined in Claim 77, and further comprising a pressurizer for pressurizing the agent inside the at least one container, wherein the at least one container comprises a valve for releasing a quantity of agent into each chamber in response to pressure inside the at least one container.

88. (Withdrawn) The apparatus defined in Claim 86, wherein the at least one elongated tube member is positioned outside the plurality of separate chambers.

89. (Withdrawn) The apparatus defined in Claim 77, wherein the at least one container comprises an inkjet print head having at least one nozzle positioned proximate to at least one opening of the housing for releasing vapor bubbles of at least one agent into the chamber through the opening when energized by control signals.

90. (Withdrawn) The apparatus defined in Claim 89, and further comprising:

- a) at least one reservoir associated with the inkjet print head for containing a volume of one or more agents; and
- b) a controller coupled to the inkjet print head and supplying control signals to the inkjet print head to control the release of one or more agents from the inkjet print head into a separate chamber.

91. (Withdrawn) The apparatus defined in Claim 76, and further comprising an access tubing connecting said backup or reserve supply container to a charging port that is attached to a lateral extension of said housing.

1-15369

92. (Withdrawn) The apparatus defined in Claim 91, wherein said backup or reserve supply container hangs free of the apparatus.

93. (Withdrawn) The apparatus defined in Claim 91, wherein said backup or reserve supply container is attached to a portion of the apparatus.

94. (Withdrawn) The apparatus defined in Claim 76, and further comprising humidity sensing means positioned in the chamber in the flow path of the gas stream.

95. (Withdrawn) The apparatus defined in Claim 94, and further comprising heating means disposed within the chamber for heating the gas.

96. (Withdrawn) The apparatus defined in Claim 95, and further comprising:

- a) temperature sensing means disposed within the chamber for sensing the temperature of the gas in the chamber; and
- b) control means connected to the temperature sensing means and to the heating means and responsive to the temperature sensing means to control electrical power to the heating means so as to regulate the amount of heat applied by the heating means to the gas within the chamber.

97. (Currently Amended) An apparatus for treating carbon dioxide gas with at least one pharmacologic agent, ~~and then heating the gas to a predetermined temperature if desired~~, the gas being received into the apparatus from a gas source, the apparatus comprising:

- a) a housing having an inlet and an outlet; and
- b) at least a single chamber within said housing having an entry port and an exit port, the entry port for connection to a source of carbon dioxide gas to receive therefrom a carbon dioxide gas stream; said the single chamber receiving a first

1-15369

quantity of a pharmacologic agent to be admixed with and carried by the carbon dioxide gas stream, the exit port for ~~removal~~ exit of the carbon dioxide gas stream from the single chamber carrying the admixed agent from the housing.

98. (Currently Amended) The apparatus defined in Claim 97, and further comprising a container containing a second quantity of the pharmacologic agent, the container in fluid communication with the chamber.

99. (Currently Amended) The apparatus defined in Claim 97, wherein the said at least one single chamber is a single chamber within said housing having an entry port communicating with the inlet of the housing, and an exit port communicating with the outlet of the housing, the entry port for connection to a gas source to receive therefrom a gas stream; said chamber receiving a quantity of a humidifying solution and a quantity of the at least one pharmacologic agent ~~to be admixed with and carried by the gas stream; and the exit port for removal of the gas stream carrying the admixed humidifying solution and agent or agents from the housing;~~ and a backup or reserve supply container for the at said least one pharmacologic agent ~~and/or humidifying solution in fluid communication with said chamber.~~

100. (Withdrawn) The apparatus defined in Claim 96, wherein said at least one chamber comprises:

a) a plurality of separate chambers within said housing, each separate chamber having an entry and an exit port through which the gas stream flows, and a separate port to receive a quantity of an agent to be admixed with the gas stream, and the exit port of another of said plurality of separate chambers carrying one or more admixed agents from the housing.

1-15369

101. (New) An apparatus for treating gas with at least one agent, the gas being received into the apparatus from a gas source, the apparatus comprising:

- a) a housing having an inlet and an outlet;
- b) a single chamber within said housing having an entry port and an exit port, the entry port for connection to a gas source to receive therefrom a gas stream; and the exit port for removal of the gas stream from the single chamber; and
- c) a quantity of the at least one agent contained within the chamber to be admixed with and carried by the gas stream for delivery to the peritoneum of a patient undergoing surgery.

102. (New) An apparatus for treating gas with at least one agent, the gas being received into the apparatus from a gas source, the apparatus comprising:

- a) a housing having an inlet and an outlet;
- b) a single chamber within said housing having an entry port and an exit port, the entry port for connection to a gas source to receive therefrom a gas stream; and the exit port for exit of the gas stream from the single chamber; and
- c) a first quantity of a solid phase pharmacologic agent contained or introduced within the single chamber and positioned such that a portion of the solid phase pharmacologic agent may be admixed with and carried by the gas stream through the exit port.

103. (New) The apparatus defined in Claim 101, where the solid phase agent is a fume or a dust.

1-15369

104. (New) An apparatus for treating a gas with at least one agent, the gas being received into the apparatus from a gas source, the apparatus comprising:

- a) a housing having an inlet and an outlet;
- b) a single chamber within said housing having an entry port and an exit port, the entry port for connection to a gas source to receive therefrom a gas stream; and the exit port for exit of the gas stream from the single chamber; and
- c) a quantity of a liquid phase pharmacologic agent contained within the single chamber and positioned such that a portion of the liquid phase pharmacologic agent may be admixed and carried by the gas stream through the exit port.

105. (New) The apparatus defined in Claim 104, wherein the liquid phase agent is a mist or a spray.

106. (New) The apparatus defined in Claim 104, wherein the liquid phase agent is wicked off or dislodged from a container.